SP 250-S

Purchase Part Number 5869001 Rental Part Number 9869001



Fully Automated IR Butt Welding Tool



90mm - 250mm (3" - 10") Size Range Single wall **Pipina** PP, PVDF **Materials** 208V / 3ph / 30A **Power**

37"x56"x56" **Dimensions** 1550 lbs. Weight 39"x58"x57" **Shipping Dimensions** 1650 lbs. **Shipping Weight**

> Please see next page for more information about power/transformer requirements for SP 250-S and SP 315-S tools.

Features

- Automated planing depth feature
- Automated fusion process
- Internal validation program
- Printer and cleanroom labels
- Ideal for shop operation
- SP 250-S operator card
- 208V to 400V power converter included in rental machines. Not included with purchased tools.

SP 315-S V3

Purchase Part Number 5869315 Rental Part Number 9869315



Fully Automated IR Butt Welding Tool



90mm - 315mm (3" - 12") Size Range Single wall **Piping** PP. PVDF **Materials** 208V / 3ph / 30A **Power**

47"x67"x58" **Dimensions** 1650 lbs. Weight 48"x68"x57" **Shipping Dimensions** 1825 lbs. **Shipping Weight**

> Please see next page for more information about power/transformer requirements for SP 250-S and SP 315-S tools.

Features

- Automated planing depth feature
- Automated fusion process
- Internal validation program
- Printer and cleanroom labels
- Ideal for shop operation
- SP 315-S operator card
- 208V to 400V power converter included in rental machines. Not included with purchased tools.

Power Transformer*

Purchase Part Number 5869003 Rental Part Number 9869003



- All Asahi/America SP 250-S (V3) and SP 315-S V3 welding tools require a transformer in order to operate. If available site power does not meet the 400v/3ph/30Amp tool power requirement, a transformer must be purchased or rented separately with the tool. See transformer purchase and rental part numbers at the bottom of this page.
- The machine comes supplied with 400V/30Amp/3ph plug when purchased
- The transformer brings the supplied 208V/30Amp/3ph power up to 400V/30Amp/3ph for the tool
- If the machine is rented, the units are already set up to correct power requirements of 208V, but sometimes customers change this depending on onsite power
- Each operating site needs to have 208V/30Amp/3ph power with correct NEMA plug where the transformer plugs in
- Tool requires uninterrupted dedicated line of power


TOOL PLUGS:

The SP 250-S and 315-S V3 tools come supplied with 400V/30Amp/3ph male plug. To operate the SP 250-S or 315-S V3 tool, a transformer is needed to bring power output from 208V up to 400V.



TRANSFORMER PLUGS:

The transformer must be purchased or rented separately. Transformer comes with a female 400V/ 30Amp/ 3ph plug and 208 V/ 30Amp/ 3ph male plug. Onsite wall/generation should have these requirements.



For questions, please reach out to our tool and rental department at 781-388-4618 or toolmanager@asahi-america.com